Claims

d	35	7
	_	

6

7

8

9

10

1

A method for forming water-soluble glass fibres, the method comprising providing a composition suitable for producing a water-soluble glass and heating said composition above the melting point of said glass to form a molten glass, cooling at least a portion of said molten glass to a preselected working temperature and then processing said molten glass having said working temperature into fibres.

11 12

13

2.

14

15

16 19 A method as claimed in either one of Claims 1 and 2 wherein said working temperature is 50-300°C

said working temperature.

above the Tq of the glass.

A method as claimed in Claim 1 wherein said

portion of said molten glass is cooled slowly to

20 21

22

23

A method as claimed in either one of Claims 1 and 4. wherein said working temperature is at least 200°C below the temperature to which the glass is initially heated.

24 25

26 5. A method as claimed in any one of Claims 1 to 4 27 wherein glass wool is formed.

28

29 6. A method as claimed in any one of Claims 1 to 5 30 wherein phosphorous pentoxide is used as the glass 31 former.

32

33 7. A method as claimed in any one of Claim 6 wherein 34 boron containing compounds are used as glass 35 modifiers.

36

37 8. A method as claimed in Claim 7 wherein B_2O_3 is used 38 as a glass modifier at a mole percentage of 15% or

less.

3 4 9.

A method as claimed in any one of Claims 1 to 8 wherein said glass is a silver-ion releasing class.

6

5

A method as claimed in Claim 9 wherein silver orthophosphate is added during manufacture of the glass as a source of silver ions.

10

11

add>